

POWER SOLUTIONS

Desiccant Air Dryer

MODEL DOMNICK HUNTER PNEUDRI MXP 106



PERFORMANCE	
Flow Rate	CFM 1100
Max Rate Operating Pressure	BAR (PSI) 12.0 (175)
Minimum Operating Pressure	BAR (PSI) 4.0 (58)
Maximum Operating Pressure	BAR (PSI) 13.8 (200)
Air Quality Class	ISO 8573:1 Class 1.2.1
Dew Point	-40C (40F)
Noise Level	75DBA
Filtration	General Purpose 0.1 Micron High Efficiency 1.0 Micron high Efficiency
DIMENSIONS	
Overall Length	2000 mm
Overall Width	1000 mm
Overall Height	2150 mm
Weight	1800 Kgs
Inlet / outlet	Connections 2" NPT Ball Valves- normally fitted with Weco fig 100
COMPLIANCE	
	Pressure Equipment Directive: 97/23/EC
	Group II Category 3 GD T5 Under 94/9/EC
	ATEX Directive 93/68/EEC , 92/31/EEC
	DNV 2.7-1
SPECIAL FEATURES	
- Unit supplied in lifting frame built to DNV 2.7-1 specification	

FULL CERTIFICATION PROVIDED

ATR EQUIPMENT SOLUTIONS

+44 (0)1224 222777
equipment@atrgroup.co.uk

ATR LIFTING SOLUTIONS

+44 (0)1224 826662
lifting@atrgroup.co.uk

ATR POWER SOLUTIONS

+44 (0)1224 775050
power@atrgroup.co.uk

SAFETY & TECHNICAL

HYDRAULICS LIMITED
+44 (0)1224 781555
enquiries@sthyd.com

UNDERWATER ENGINEERING

SERVICES
+44 (0)1358 789808
sales@uesltd.net